

ordering quote request

COMPANY INFORMATION

Using the cutting edge order form, starting from the left top corner put a check in either the order or quote box, enter PO# and/or job name. Fill out company information, i.e., company name, mailing address, ship to address and contact name. Enter the phone#, fax#, date ordered and required date.

DOOR SPECIFICATIONS

Start by entering the wood species, inside profile (#), panel raise (letter) outside profile (#). In the style box, enter the desired number from the arches sheet.

Start with the top left hand column. Enter door style, qty, and size (width x height). Once all of the doors are entered, enter drawer front style, qty, and size (width x height).

FRAMES

An open frame is identified with an F beside the style # for an open frame and an M (with the # of lites beside it) for a mullion frame. If a French Mullion (9 lite offset) is desired, please denote this by placing a 9 beside the M in the style box.

DRAWER FRONTS

We do three styles of drawer fronts, they are slab, 3 piece and 5 piece.

These are specified as follows:

- Slab – the name SlabD is placed in the Style box
- 3 piece fronts – the name is Slab3D is placed in the Style box
- 5 piece fronts – carry the style number from the doors forward with a D (example: 100D)

CUSTOM PANELS

Cutting Edge has the ability to create unique custom panels. Please call us to discuss your custom panel today.

specifications

DOORS

- **STILES & RAILS** - Come standard at 2 ¼". Custom widths are available but must be specified in the additional requirements box on the bottom right hand of the order form.

Doors under 7½" will have narrower stiles. This is to leave enough centre panel to make the door look proportionate. If you wish to have this modified please contact us.

- **ARCHES** – Any arch over 24", a template charge will apply. To retain the shoulder on the arch and 2 ¼" stiles, the minimum width is 12". From 12" to 8", the shoulder of the arch will be trimmed. From 8" down to 6" the width of the stiles will be reduced.

The minimum height for a door with an arch is 9 7/8"

- **CENTRE RAILS** – Doors 43" and over in height will have a centre rail installed at the midpoint of the door. This rail can be placed in any location in the door. This must be specified with a sketch or a note in the additional requirements box. It can also be requested with no centre rail. Cutting Edge is unable to warrant these doors for warp in the event no centre rail is requested.
- **CENTRE STILES** – Doors 40" and over in width will be given a centre stile. We recommend the following:
 - 40" – 45" have one centre stile with equal spacing
 - 45" – 60" have 2 centre stiles with equal spacing
 - 60" – 80" have 3 centre stiles with equal spacing

MULLION FRAMES

Mullion frames less than 24" in height will be given 4 lites; 24" – 39" will be given 6 lites; 40" & larger will be given 8 lites.

CUSTOM PANELS

There are many options available for custom panels - wider rails, stiles, angled 5 piece panels, range hood components. It is preferred if a sketch can be sent over with the required details.